

WB10K / WB12K
10KWB / 30KWB

WATERBLAST
ISO 9001 MFG



APPLICATION

TUBE

Mineral, vegetable, hydraulic and glycol based fluid resistant synthetic rubber

COVER

Hydraulic oil, abrasion and weather resistant synthetic rubber

REINFORCEMENT

6 spiral high tensile steel wires

BRANDING

10K/WP, 25K/BP WATERBLAST
12K/W, 30K/BP WATERBLAST

SAFETY FACTOR

2.5:1

TEMPERATURE

14 °F to 158 °F

Very high pressure hose for water scaling and jetting systems.

WB10K

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	WORKING PRESSURE (PSI)	MINIMUM BURST PRESSURE	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
WB10K-12	10KWB-12	3/4	1.27	10,000	25,000	1.18	8.6	VARIOUS
WB10K-16	10KWB-16	1	1.5	10,000	25,000	1.33	11.81	VARIOUS

WB12K

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	WORKING PRESSURE (PSI)	MINIMUM BURST PRESSURE	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
WB12k-04	30KWB-04	1/4	0.7	12,000	30,000	0.4	4.92	VARIOUS
WB12k-06	30KWB-06	3/8	0.795	12,000	30,000	0.48	5.9	VARIOUS
WB12k-08	30KWB-08	1/2	0.933	12,000	30,000	0.8	7.09	VARIOUS

ASSEMBLY FABRICATION AND PRESSURE TESTING/CERTIFICATION AVAILABLE.