

**PG600**  
1C8817

## PLASTER, GROUT AND CONCRETE HOSE

ISO 9001 MFG



### APPLICATION

#### TUBE

Black abrasion resistant anti-static natural rubber

#### COVER

Black abrasion, ozone, weather resistant pin-pricked SBR

#### REINFORCEMENT

High tensile synthetic textile cord

#### BRANDING

Brown longitudinal stripe: (PSI per Size)  
Plaster/Grout Concrete Spray

#### ELECTRIC CONTINUITY

Anti-static copper wire

#### SAFETY FACTOR

3:1

#### TEMPERATURE

-40 °F to 158 °F

Designed for high pressure spraying plaster grout, sand, gypsum and ready mix concrete. 1233 PSI available. Please call customer service for specification details.

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	PLIES	WORKING PRESSURE (PSI)	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
PG600-125	1C8817-125	1-1/4	1.9	2	800	0.77	7.87	100
PG600-150	1C8817-150	1-1/2	2.2	4	800	1.1	9	100
PG600-200	1C8817-200	2	2.75	4	800	1.45	12	100
PG600-250	1C8817-250	2-1/2	3.3	4	800	1.74	14.76	100
PG600-300	1C8817-300	3	4.01	4	650	2.72	17.1	100
PG600-400	1C8817-400	4	5.11	4	650	3.96	23.62	100
PG600-500	1C8817-500	5	6.1	6	650	4.66	29.5	100

200/FT LENGTHS AVAILABLE ON SPECIAL ORDER. FULL FLOW INTERNALLY EXPANDED OR SWAGED. FABRICATION AND TESTING AVAILABLE.