

PD250
1C72

250 PSI PETROLEUM DISCHARGE HOSE
ISO 9001 MFG



APPLICATION

TUBE

Black oil and petroleum resistant neoprene

COVER

Red Abrasion, ozone, weather and petroleum resistant neoprene

REINFORCEMENT

High tensile synthetic textile cord with antistatic copper wire

BRANDING

Black longitudinal stripe: 250 PSI petroleum discharge

SAFETY FACTOR

3:1

TEMPERATURE

-22 °F to 180 °F continuous

A

PETROLEUM HOSE

For delivery of petroleum products up to 50% aromatic content.

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	PLIES	WORKING PRESSURE (PSI)	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
PD250-100	1C72-100	1	1.46	2	250	0.57	N/A	100/200
PD250-125	1C72-125	1-1/4	1.74	2	250	0.69	N/A	100/200
PD250-150	1C72-150	1-1/2	1.97	4	250	0.8	N/A	100/200
PD250-200	1C72-200	2	2.6	4	250	1.32	N/A	100/200
PD250-250	1C72-250	2-1/2	3.12	4	250	1.74	N/A	100/200
PD250-300	1C72-300	3	3.63	4	250	1.91	N/A	100/200
PD250-400	1C72-400	4	4.65	4	250	2.69	N/A	100/200
PD250-600	1C72-600	6	6.8	4	250	4.53	N/A	100/200

COUPLINGS: CAM & GROOVE OR COMBINATION NIPPLE. ASSEMBLY FABRICATION & TESTING AVAILABLE.