

**TC300**  
1C27

**300 PSI TANK CLEANING HOSE**  
ISO 9001 MFG

A

PETROLEUM HOSE



### APPLICATION

#### TUBE

Black EPDM rubber

#### COVER

Black EPDM weather and detergent resistant rubber

#### REINFORCEMENT

High tensile synthetic textile cord with antistatic wire

#### BRANDING

Yellow marking rings every 5 feet: 300 PSI Tank Cleaning

#### ELECTRIC CONTINUITY

Assured by two wires embedded in the carcass, crossing and touching each other

#### SAFETY FACTOR

3:1

#### TEMPERATURE

-22 °F to 200 °F

Suitable for cleaning of storage tanks afloat or onshore. A durable hose with a high degree of resistance to kinking, abrasion and the wide range of chemicals used in this application.

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	PLIES	WORKING PRESSURE (PSI)	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
TC300-150	1C27-150	1-1/2	2.12	4	300	0.97	9	100/200/400
TC300-200	1C27-200	2	2.8	4	300	1.55	12	100/200/400

**COUPLINGS:** CAM & GROOVE OR COMBINATION NIPPLE. ASSEMBLY FABRICATION & TESTING AVAILABLE. 400 FT LENGTHS AVAILABLE ON REQUEST. CHECK FOR LEAD TIMES.