

ST250*
1C58B

250 PSI-450°F STEAM HOSE
ISO 9001 MFG



APPLICATION

TUBE

Extruded black EPDM resistant to saturated steam

COVER

Black or red abrasion, heat, steam, oil, ozone and weather resistant pin-pricked special synthetic rubber

REINFORCEMENT

High tensile steel wire

BRANDING

Steam Hose 250 PSI 450°F drain after use

SAFETY FACTOR

10:1

TEMPERATURE

-40 °F to 450 °F

Designed to handle saturated steam in oil refineries, steel mills, chemical plants, shipyards and a wide range of industries.

*Available in Red (R) or Black (B).

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	WORKING PRESSURE (PSI)	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
ST250* - .50	1C58-.50	1/2	0.94	250	0.36	2.76	100
ST250* - .75	1C58-.75	3/4	1.26	250	0.48	3.94	100
ST250* - 100	1C58-100	1	1.52	250	0.64	5.51	100
ST250* - 125	1C58-125	1-1/4	1.81	250	0.85	7.9	100
ST250* - 150	1C58-150	1-1/2	2.05	250	1.06	9.84	100
ST250* - 200	1C58-200	2	2.64	250	1.6	13.78	100
ST250* - 250	1C58-250	2-1/2	3.13	250	2	17.72	100
ST250* - 300	1C58-300	3	3.66	250	2.61	21.65	100
ST250* - 400	1C58-400	4	4.88	250	4.43	29.53	100

ONLY AVAILABLE WITH GROUND JOINT AND BOSS CLAMP FITTINGS PER NAHAD GUIDELINES FOR STEAM HOSE.