

WB16K / WB18K
40KWB / 45KWB

WATERBLAST
ISO 9001 MFG



APPLICATION

TUBE

Mineral, vegetable, hydraulic and glycol based fluid resistant synthetic rubber

COVER

Hydraulic oil, abrasion and weather resistant synthetic rubber

REINFORCEMENT

4 spiral high tensile steel wires

BRANDING

16K/WP, 40K/BP WATERBLAST
18K/W, 45K/BP WATERBLAST

SAFETY FACTOR

2.5:1

TEMPERATURE

14 °F to 158 °F

Very high pressure hose for water scaling and jetting systems.

WB16K

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	WORKING PRESSURE (PSI)	MINIMUM BURST PRESSURE	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
WB16K-08	40KWB-08	3/4	0.97	16,000	40,000	0.814	9.05	VARIOUS

WB18K - 4 SPIRAL RUBBER HOSE

NEW PART NO.	LEGACY PART NO.	I.D. (IN)	O.D.* (IN)	WORKING PRESSURE (PSI)	MINIMUM BURST PRESSURE	WEIGHT FT/LB	MBR (IN)	STANDARD LENGTH/FT
WB18K-04	45KWB-04	1/4	0.692	18,000	45,000	0.412	7.87	VARIOUS
WB18K-06	45KWB-06	3/8	0.803	18,000	45,000	0.61	8.27	VARIOUS
WB18K-08	45KWB-08	1/2	1.09	18,000	45,000	1.22	9.84	VARIOUS

ASSEMBLY FABRICATION AND PRESSURE TESTING/CERTIFICATION AVAILABLE.